

ОПТИЧЕСКИЕ ПРИБОРЫ

The best vision for 1.8X is 20-30cm; 2.3X at 10-14cm and 4.8X at 8-10cm and the light will be in the center spot at 8-10cm

① 1.8X
②+③ 2.3X
①+②+③ 4.8X

①+②+③ THREE-IN..4.8X
②+③ OVERLAPPING GLASS..2.3X
① SINGLE..1.8X

Magnification	Lens size (mm)	Individual packing
Single: 1.8X	Square: 91x29	Blister card
Overlapping: 2.3X Three-in: 4.8X	Round: 28	

- Light weight. Frame is made of durable impact resistant material.
- The comfortable headband is fully adjustable to fit any size.
- Easy to adjusting visor to most comfortable position.
- Bring object into focus.
- Easy to changing lenses.
- Circumference: 640mm

Бинокляры 8PK-MA003N
возможности увеличения: x1,8;2.3;4.8 , двусторонняя подсветка

SIZE: 2" x 3-1/2" (50 x 90mm)
OAL: 8-1/2"-19-1/4" (216 x 490mm)

All-angle ball joint mirrors with stainless steel mirror backs. Visual inspection of hidden areas. Double ball joint links swivel mirrors for viewing to 360°. Made of tempered spring steel to move freely and hold desired position. Replaceable, plated, copper-backed, clear-view mirrors. Non-rotating inner hex rods prevent mirrors from swinging out of alignment. Insulating vinyl grip on 1PK-390G, one (1PK-390), don't have vinyl.

Individual packing
Blister card

Зеркало инспекц. 1PK-390G
размер зеркала 50x90 мм, рабочая длина 216x490 мм, с вращением на 360 град.

- 5 diopter (2.25X magnification) glass lens.
- Even, shadow-free light under the magnifying lens with 22-watt circular fluorescent tube makes it easier for you to see and enjoy the activities longer.
- Spring balanced adjustable arm for easy maneuverability and positioning.
- Heavy duty cast bench clamp mounts to any bench top.
- Adjustable clamp base fits up to 65mm thick surfaces.
- Comes with a protection cover to produce sharp image over a wide viewing area.

Model No.	Voltage	Lens	Illumination	Lens size	Standard plug	Individual packing
8PK-F1205CA	AC 120V	5D	22W	ø127mm	E	Color Box
8PK-F1205CB	AC 230V				B	

• Approval: AC 120V: AC 230V:

Линза с подсветкой 8PK-F1205CB
на кронштейне, 12см, 5 диоптрий, кольцевая люминесцентная лампа

- 3 diopter (1.75X magnification) glass lens.
- New improved clamp-on sponge design for firm contact on smooth surfaces and mounts to any bench or desktop.
- Even, shadow-free light under the magnifying lens with 9-watt fluorescent tube will make it easier for you to see and enjoy the activities longer.
- Spring balanced adjustable arm for easy maneuverability and positioning.
- Easy to replace the fluorescent tubes.

Model No.	Voltage	Lens	Illumination	Lens size	Standard plug	Individual packing
8PK-F150NA	AC 120V	3D	2x9W	ø190x155mm	E	Color Box
8PK-F150NB	AC 230V				B	

• Approval: AC 120V: AC 230V:

Линза с подсветкой 8PK-F150NB
прямоугольная 18x15см, 3 диоптрии, улучшенная обзорность, 2 лампы дневного света







  

Easy clamp Tilt up and down Pan left and right

- 5 diopter (2.25X magnification) glass lens.
- Even, shadow-free light under the magnifying lens with 22-watt T5 circular fluorescent tube will make it easier for you to see and enjoy the activities longer.
- All metal housing mounted on a spring balanced arm that stays set in any position.
- Clamps easily and securely onto most flat surfaces up to 65mm thick.
- Dust-proof cover for lens protection.

Model No.	Voltage	Lens	Illumination	Lens size	Standard plug	Individual packing
MA-1215CA	AC 120V	3D	22W/T5 G10q	ø127mm	A	Color Box
MA-1215CF	AC 230V				F	

Линза с подсветкой
MA-1215CF
кольцевая подсветка,
увеличение х5,
кронштейн пантограф,
крепление к столу





  

- 5 diopter (2.25X magnification) glass lens.
- Even, shadow-free light under the magnifying lens with 22-watt T5 circular fluorescent tube will make it easier for you to see and enjoy the activities longer.
- The flexible gooseneck allows you to angle and point the light to where you need it most.
- Clamps easily and securely onto most flat surfaces up to 65mm thick.
- Dust-proof cover for lens protection.

Model No.	Voltage	Lens	Illumination	Lens size	Standard plug	Individual packing
MA-1225CA	AC 120V	5D	22W/T5 G10q	ø127mm	A	Color Box
MA-1225CF	AC 230V				F	

Линза с подсветкой
MA-1225CF
кольцевая подсветка,
увеличение 5X,
кронштейн гибкая
трубка